

DM0408

Multi-Purpose low Speed Centrifuge

Features

- Quiet, compact, and convenient with LCD display
- Maximum up to 4000rpm Speed can be set in RPM/RCF, with 3 customizable routine programs (Blood, Urine & Faecal)
- 3 acceleration level & 4 level deceleration
- Maximum capacity 50mL × 4, Accommodating different sizes of blood collection tubes and centrifuge tubes suitable for swing out rotor and angle rotor
- Automatic internal diagnosis and self-detection
- Maintenance-free brushless DC motor

Applications

Multi-purpose low speed centrifuge are versatile and can be used in applications from clinical to biochemical for qualitative analysis of serum, plasma, blood, and urine.

| Specifications | DM0408 |
|---------------------------|---|
| Speed range | 300-4000rpm increment: 100rpm |
| Max. RCF | 1900×g |
| Speed accuracy | ±100rpm |
| Rotor | Angel 8×15mL(Default), Angel 12×10mL |
| Run time | 1-99min, HOLD |
| Motor | Brushless DC motor |
| Display | LCD |
| Program | Blood: 3200rpm, 10min Urine: 1800rpm, 5min Faecal: 1300rpm, 10min |
| Safety Device | Automatic internal diagnosis |
| Acceleration/deceleration | 25s ↑ 35s ↓ |
| Power Requirements | Single phase, 100-240V, 50Hz/60Hz, 85W |
| Dimension(W×D×H) | 286×367×227mm |
| Weight | 9.2kg |
| Noise Level | ≤60dB(A) |



A8-15P

Cat. No.19400084

for DM0424/DM0408

Max. Speed: 4000rpm
Rotor capacity: 15mL × 8
Rotor material: High strength plastic
Default adaptor: A15P22



A12-10P

Cat.No.19400068

for DM0424/DM0408 DM0412

Max.speed : 4000rpm
Rotor capacity: 8×15mL or 12×10mL
Rotor material: High strength plastic



A15P30

Cat. No.19500024

50mL change 15mL adapter,
Adapted to 17×120mm centrifuge
tube, 13/16×100mm blood
collection tube 4pcs/pk,



A15P22

Cat. No.19500021

15mL adapter for 17×120mm
centrifuge tube, 13/16×100mm
blood collection tube 24 pcs/pk,
for S6-15, A24-15P, A8-15P

